

What is claimed is:

1. A nail magazine structure of a power nailer having an interior for depositing a row of nails and having an end joined with a nailer nozzle, and comprising:
 - 5 a first magazine sheet;
 - a second magazine sheet disposed on the first magazine sheet and relative to the first magazine sheet to move; and
 - a plurality of nail pushing units parallel to one another and disposed between the first magazine sheet and the second
 - 10 magazine sheet;
 - wherein each nail pushing unit includes a pushing sheet, a flexible element for providing flexible force to push the pushing sheet, and a supporting portion disposed at a side of the pushing sheet for near supporting an end of the row of nails.
- 15 2. The nail magazine structure of a power nailer according to claim 1, wherein the pushing sheet of the nail pushing unit is provided with a shaft sleeve for depositing an end of the flexible element.
3. The nail magazine structure of a power nailer according to
- 20 claim 1, wherein the flexible element of the nail pushing unit includes an axial rod and a spring put around the axial rod.
4. The nail magazine structure of a power nailer according to claim 2, wherein the flexible element of the nail pushing unit includes an axial rod and a spring put around the axial rod.

5. The nail magazine structure of a power nailer according to claim 1, wherein the pushing sheet of the nail pushing unit is further provided with an expanding surface perpendicular to the supporting portion.
- 5 6. The nail magazine structure of a power nailer according to claim 1, wherein the second magazine sheet is provided with a plurality of first grooves for disposing the flexible elements of the nail pushing unit.
7. The nail magazine structure of a power nailer according to
10 claim 1, wherein the second magazine sheet has a surface being flat for disposing a row of nails without head.
8. The nail magazine structure of a power nailer according to claim 1, wherein the second magazine sheet is provided with a plurality of second grooves disposed in a surface thereof for
15 disposing a row of T-shaped nails.